

SNLXVKIT SPECIFICATION

About Invicta Xero Vent Kits

Designed to support compliance with AS/NZS 3001.2:2022 caravan electrical installation requirements, our integrated Vent Kit for the Invicta Xero range provides a dedicated pathway for battery vent gases to be safely discharged outside the vehicle. This innovative solution simplifies battery installation, reduces the need for complex battery enclosures, and gives caravan manufacturers and installers greater flexibility when positioning lithium batteries within RVs and caravans. When installed in accordance with our instructions, the Vent Kit helps streamline compliance while enhancing safety and installation efficiency.

Features & Benefits

- Helps installers comply to AS/NZS 3001.2:2022 when installing Invicta Xero lithium batteries in caravan applications.
- Insulated hose for venting high temperature and high pressure gasses.
- Male and female threaded hose barbs for easy attachment to the Invicta Xero vent port.
- Plastic cable gland for secure connection and separation to external environment.
- Stainless steel hose clamp ensures tight connection between hose and barb.

Hose length	3M
Hose outside diameter	13mm
Brass male hose barb (threaded)	SNLX Vent Port
Brass female hose barb (threaded)	8mm
Rubber washer	4mm
Stainless steel hose clamp	9-16mm
Plastic cable gland	25mm

